

Benefits

1. superior engine protection in stop-and-go environment
2. BIZOL W-guard technology for wear prevention
3. BIZOL COMB LubriBoost technology for maxing up oil film strength and fuel efficiency

Product Description

Our German engineers have developed a customized top-tier synthetic motor oil with an effective formulation for optimal engine protection in urban traffic when 75% of engine wear occurs because of frequent start-stops, rapid acceleration and short-haul trips. This formulation provides an extra layer of protection for turbocharged and supercharged gasoline and diesel engines equipped with DPF and TWC systems and automatic start-stop systems.



Base Oil

Fully Synthetic

Specifications/Approvals & Recommendations

ACEA A1/B1 | API SN | ILSAC GF 5

Ford WSS-M2C-930-A/WSS-M2C-945-A | GM 6094 M

Available Packages

1 L Art. 81070

4 L Art. 81076

Technical Data

Name	Value	Method
Viscosity class SAE	5W-20	
Colour	green	
Viscosity at 40 °C	49,1 mm ² /s	ASTM D 7042
Viscosity at 100 °C	8,8 mm ² /s	ASTM D 7042
Viscosity index	160	ASTM D 2270
Density at 15 °C	850 kg/m ³	DIN EN ISO 12 185

Technical Data

Name	Value	Method
Pour Point	-40 °C	ISO 3016
Flash Point (Cleveland)	210 °C	ISO 2592
Total base number (TBN)	6,6 mg KOH/g	ASTM D 2896
Sulfate ashes	0,67 %	DIN 51 575
Viscosity at -30°C	4900 mPa,s	ASTM D 5293

Instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.