

## Benefits

1. developed especially for VW gasoline and diesel engines with DPF
2. increased oil change intervals are possible
3. optimal wear protection and extended service life of the engine are possible

## Product Description

**BIZOL Technology 5W-30 507** is a modern high-performance, long-life motor oil with reduced ash content. This oil is universally formulated in compliance with the requirements of VW motors. It is backward compatible to the previous generations of motors under consideration of recommended oil change intervals. It is suitable for VW vehicles with and without extended oil change intervals, as well as for FSI engines and other types of diesel engines with diesel particulate filter (DPF). Can be applied in diesel engines, such as V10 R5-TDI with pump injector with and without DPF built since 06/2006.



## Base Oil

Fully Synthetic

## Specifications/Approvals & Recommendations

ACEA C3 | API SM/CF

MB 229.51 | BMW LL 04 | VW 504 00/507 00 | Porsche C30 |

GM LL B-025 | Renault RN 0700/RN 0710

## Available Packages

1 L Art. 85820    5 L Art. 85821    20 L Art. 85822    60 L Art. 85823

200 L Art. 85824

## Technical Data

| Name                | Value                   | Method      |
|---------------------|-------------------------|-------------|
| Viscosity class SAE | 5W-30                   |             |
| Viscosity at 40 °C  | 65,0 mm <sup>2</sup> /s | ASTM D 7042 |
| Viscosity at 100 °C | 11,5 mm <sup>2</sup> /s | ASTM D 7042 |

## Technical Data

| Name                    | Value                 | Method            |
|-------------------------|-----------------------|-------------------|
| Viscosity index         | 172                   | ASTM D 2270       |
| Density at 15 °C        | 850 kg/m <sup>3</sup> | DIN EN ISO 12 185 |
| Pour Point              | -42 °C                | ISO 3016          |
| Flash Point (Cleveland) | 235 °C                | ISO 2592          |
| ASTM colour number      | L4,0                  | ASTM D1500        |
| Sulfate ashes           | 0,50 %                | DIN 51 575        |
| Total base number (TBN) | 6,6 mg KOH/g          | ASTM D 2896       |

## Instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.