



Mobil Almo 500 Series

Mobil Industrial , Russia

Pneumatic Rock Drill and Tool Lubricants

Product Description

Mobil Almo 500 Series lubricants are premium quality high performance products primarily intended for the lubrication of pneumatically operated rock drills in underground and surface mining operations. The Mobil Almo Series oils are formulated from high quality base stocks and additives, which provide excellent chemical stability and good protection against wear and corrosion. They offer an optimum balance of adhesiveness, yet are emulsifiable enough to pick up moisture carried in the air stream reducing the negative effects of water on wear and corrosion. They do not form gummy deposits that could cause sluggish valve action. Even in the presence of water, the Mobil Almo 500 Series oils have good preferential metal-wetting properties that maintain continuous oil films. These properties in combination with high EP characteristics help provide excellent lubrication resulting in long equipment life.

Mobil Almo 500 Series possess high viscosity indexes and low pour points to ensure good lubrication at the low temperatures resulting from air expansion and guard against icing stoppages while providing adequate films on drill parts that may operate at high temperatures. Oil fog generation levels are extremely low.

Features and Benefits

The Mobil Almo 500 Series oils provide an optimum performance balance which assures long equipment life and minimal maintenance costs. Their excellent wear protection characteristics and ability to provide adequate lubrication in the presence of water not only reduces wear but protects against rust and corrosion. Their good chemical stability prevents sludge and deposit formation reducing the need for frequent maintenance.

Features	Advantages and Potential Benefits
Effective Chemical Stability	Reduce sludge and deposit formation Improves valve operation
Desired Emulsifiable Properties	Effective lubrication in presence of water
High Viscosity Index	Provides good lubrication at both high and low temperatures
Excellent Load Carrying Ability and Anti-Wear Protection	Reduces component wear Prolongs equipment life Reduces maintenance costs
Very Good Adhesive Characteristics	Protects metal surfaces from corrosion Provides good lubricant films under all conditions
Rust and Corrosion	Longer tool life Increased tool performance

Applications

Mobil Almo 500 Series oils are recommended for use in all pneumatically operated rock drills in both underground and surface mining as well as in contractor and other industrial applications. They are suitable for percussive- and rotary- type tools. The viscosity grades allow selection for year-round use where seasonal ambient temperature variations are extreme.

- Pneumatically operated rock drills in underground and surface mining operations
- Pneumatically operated drills and jack hammers in highway construction and building operations
- Rock drills in quarry operations
- Percussion and rotary air-operated tools in industrial applications

Typical Properties

	Mobil Almo 524	Mobil Almo 525	Mobil Almo 527	Mobil Almo 529	Mobil Almo 530	Mobil Almo 532

	Mobil Almo 524	Mobil Almo 525	Mobil Almo 527	Mobil Almo 529	Mobil Almo 530	Mobil Almo 532
ISO Viscosity Grade	32	46			220	320
Viscosity, ASTM D 445						
cSt @ 40°C	32	46	100	172	220	320
cSt @ 100°C	5.5	7.3	11.5	16.5	19.7	24.9
Viscosity Index, ASTM D 2270	108	105	102	102	100	99
Pour Point, °C, ASTM D 97	-51	-30	-27	-24	-24	-21
Flash Point, °C, ASTM D 92, min	170	188	220	220	220	232
Density @ 15.6°C, ASTM D 4052, kg/L	0.880	0.883	0.899	0.893	0.898	0.902

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Switzerland Use: Toxicity class: free BAG T No.: 611500

The Mobil logotype, the Pegasus design and Almo are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

11-2019

ExxonMobil Lubricants & Specialties Europe, подразделение ExxonMobil Petroleum & Chemicals BVBA. Настоящая информация относится только к продуктам, поставляемым в Европу, включая Турцию, и страны бывшего Советского Союза.

ООО «Мобил Ойл Лубрикантс»: 123242, Москва, Новинский бульвар, д.31

+ 7 (495) 232 22 23

Указанные значения показателей являются типичными для результатов, лежащих в пределах нормальных производственных допусков, но не являются составной частью спецификации или норм. На обычном производстве и при изготовлении на разных заводах возможны отклонения, которые не влияют на эксплуатационные характеристики. Содержащаяся здесь информация может быть изменена без уведомления. Не все продукты могут быть доступны на местном рынке. За дополнительной информацией обращайтесь к местному представителю ExxonMobil или посетите www.exxonmobil.com

ExxonMobil включает в себя множество аффилированных и дочерних компаний, многие из которых содержат в своем наименовании Esso, Mobil или ExxonMobil. Ничто в настоящем документе не подразумевает отмену или преобладания над корпоративной независимостью местных организаций. Ответственность и отчетность за действия на местах остаются за местными аффилированными организациями ExxonMobil.

Energy lives here™

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved