

AVISTA pure CF-4 SAE 15W-50

Engine oil for the mixed vehicle fleet (petrol older than 2001), where the requirements of API specification CF-4/SJ must be met.

APPLICATION

- Commercial vehicles, cars (2001 and older), petrol, diesel

CHARACTERISTICS

- Aging resistance
- stability of viscosity
- fuel-saving
- low exhaust gas emissions
- engine cleanliness
- longer maintenance interval

RECOMMENDATIONS

API	CF-4
API	SJ

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		15W-50
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.850 – 0.880
Kin. Viscosity @ 100 °C	DIN 51562-1	mm ² /s	17.3 – 18.7
Viscosity Index	DIN ISO 2909		min. 150
Total Base Number	DIN ISO 3771	mg KOH/g	7.3 – 9.3
Dyn. Viscosity @ -20°C	DIN 51377	mPa*s	max. 7,000
Flash point COC	DIN ISO 2592	°C	min. 200
Pour Point	DIN ISO 3016	°C	max. -33

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Nnummer 2)