

Benefits

1. reduction of CO2 emissions
2. excellent lubricating properties minimize wear of engine components
3. compatible with downsized engines

Product Description

BIZOL Allround 0W-20 is a high quality hydrocracked synthetic oil developed to reduce CO2 emissions. This low-viscosity engine oil perfectly suits downsized gasoline engines with and without turbocharger und modern emission control systems. The main focus in the development of this modern engine oil was on reducing oil consumption and pollutant emissions. This was achieved by fusing quality base oil and premium additives. **BIZOL Allround 0W-20** also has excellent dispersing and antioxidant properties ensuring a long-lasting cleanliness of all engine components, a long engine life and long maintenance intervals. It minimizes the risk of LSPI.



Base Oil

HC-Synthetic

Specifications/Approvals & Recommendations

API SN | ILSAC GF 5

GM DEXOS 1 Gen. 2/6094 M | Chrysler MS-6395 | Ford WSS-M2C-945-A

Available Packages

1 L Art. 85830

4 L Art. 85836

5 L Art. 85831

Technical Data

Name	Value	Method
Viscosity class SAE	0W-20	
Viscosity at 40 °C	45,1 mm ² /s	ASTM D 7042
Viscosity at 100 °C	8,5 mm ² /s	ASTM D 7042
Viscosity index	169	ASTM D 2270

Technical Data

Name	Value	Method
Density at 15 °C	840 kg/m ³	DIN EN ISO 12 185
Pour Point	-42 °C	ISO 3016
ASTM colour number	L3,0	ASTM D1500
Total base number (TBN)	7,4 mg KOH/g	ASTM D 2896