

Benefits

1. increased oil change intervals
2. reduction of oil consumption
3. reliable and long-lasting protection against corrosion

Product Description

BIZOL Allround 10W-40 CI-4 is to be used in heavy-duty diesel engines with or without turbochargers. This low friction engine oil has been developed for engines without diesel particle filter, but can also be used in engines with exhaust gas recirculation systems (EGR). Modern technology in combination with unique base oils provides this product with its outstanding characteristics such as reduced friction and wear protection and helps prolonging the intervals between oil changes.



Base Oil

HC-Synthetic

Specifications/Approvals & Recommendations

ACEA A3/B4/E7 | API CI-4/SL | Global DHD-1 | JASO DH-1
MB 228.3/229.1 | MAN M 3275 |
Cummins CES 20076/CES 20077/CES 20078 | Volvo VDS III |
Renault Truck RLD-2 | MTU Type 2 | Deutz DQC III | Caterpillar ECF-1A |
Valtra CR | MACK EO-M Plus

Available Packages

1 L Art. 85320 4 L Art. 85326 5 L Art. 85321 20 L Art. 85322
60 L Art. 85323 200 L Art. 85324

Technical Data

Name	Value	Method
Viscosity class SAE	10W-40	
Viscosity at 40 °C	89,8 mm ² /s	ASTM D 7042
Viscosity at 100 °C	13,3 mm ² /s	ASTM D 7042
Viscosity index	149	ASTM D 2270

Technical Data

Name	Value	Method
Density at 15 °C	870 kg/m ³	DIN EN ISO 12 185
Pour Point	-39 °C	ISO 3016
ASTM colour number	L4,5	ASTM D1500
Total base number (TBN)	11,5 mg KOH/g	ASTM D 2896