

Benefits

1. great resistance to high shear loads even in very high speed ranges
2. optimum lubrication even under extremely high temperatures
3. very low evaporation loss

Product Description

BIZOL Allround 10W-60 is fully synthetic high-performance engine oil. The synthetic components give it an extremely high quality level that is particularly useful for engines that are exposed to high thermal stress. Even particularly strong shear loads in high speed ranges do not affect the stability of the oil's lubricating film. State-of-the-art detergent additives prevent the formation of laquered deposits on piston rings and provide for a long-lasting engine cleanliness.



Base Oil

Fully Synthetic

Specifications/Approvals & Recommendations

API SL/CF | JASO MA-2

Available Packages

1 L Art. 89320

4 L Art. 89326

Technical Data

Name	Value	Method
Viscosity class SAE	10W-60	
Viscosity at 40 °C	164,0 mm ² /s	ASTM D 7042
Viscosity at 100 °C	23,0 mm ² /s	ASTM D 7042
Viscosity index	170	ASTM D 2270
Density at 15 °C	850 kg/m ³	DIN EN ISO 12 185
Pour Point	-39 °C	ISO 3016
Flash Point (Cleveland)	220 °C	ISO 2592

Technical Data

Name	Value	Method
ASTM colour number	L5,0	ASTM D1500
Sulfate ashes	0,90 %	DIN 51 575
Total base number (TBN)	8,2 mg KOH/g	ASTM D 2896