

Benefits

1. best protection against soot thickening
2. prevents deposits on the pistons-rings
3. long lifetime of the engine oil

Product Description

BIZOL Allround 5W-40 is a modern high-performance engine oil that grants optimal protection against wear, premature aging and sludging. The selection of friction modifying and corrosion inhibiting additives as well as the use of high-quality base oils provide for excellent lubricity especially under extreme conditions. Thus BIZOL Allround 5W-40 ensures permanent protection from deposits on parts which are prone to wear. This engine oil allows for extended maintenance intervals.



Base Oil

HC-Synthetic

Specifications/Approvals & Recommendations

ACEA A3/B4 | API SN/CF
MB 229.3 | BMW LL 01 | VW 502 00/505 00 | GM LL A-025/LL B-025 |
Porsche A40 | Renault RN 0700/RN 0710 | Fiat 9.55535 N2 |
Peugeot B71 2296

Available Packages

1 L Art. 85220 4 L Art. 85226 5 L Art. 85221 20 L Art. 85222
60 L Art. 85223 200 L Art. 85224

Technical Data

Name	Value	Method
Viscosity class SAE	5W-40	
Viscosity at 40 °C	87,0 mm²/s	ASTM D 7042
Viscosity at 100 °C	14,5 mm²/s	ASTM D 7042
Viscosity index	174	ASTM D 2270

Technical Data

Name	Value	Method
Density at 15 °C	860 kg/m ³	DIN EN ISO 12 185
Pour Point	-39 °C	ISO 3016
ASTM colour number	L4,0	ASTM D1500
Total base number (TBN)	10,8 mg KOH/g	ASTM D 2896
Sulfate ashes	0,90 %	DIN 51 575