BIZOL Moto 20W-50

Martin-Buber-Straße 12, 14163 Berlin, Germany www.bizol.com

Benefits

- 1. excellent thermal protection
- 2. excellent for motorcycle with wet clutches
- 3. excellent wear protection

Product Description

BIZOL Moto 20W-50 is a high quality all year round motorcycle oil for fourstroke engines. The combination of mineral base oil with advanced additives provides outstanding wear protection and high thermal stress resistance. It can be used with engines with wet clutches according to JASO MA.



Ver. 2020-11-26

Base Oil

Mineral

Specifications/Approvals & Recommendations

API SJ | JASO MA

Available Packages

1 L Art. 18320 4 L Art. 18326

Technical Data

Name	Value	Method
Viscosity class SAE	20W-50	
Viscosity at 40 °C	165,0 mm²/s	ASTM D 7042
Viscosity at 100 °C	19,1 mm²/s	ASTM D 7042
Viscosity index	131	ASTM D 2270
Density at 15 °C	888 kg/m³	DIN EN ISO 12 185
Pour Point	-24 °C	ISO 3016
Flash Point (Cleveland)	220 °C	ISO 2592

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for a specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.

BIZOL Moto 20W-50

Martin-Buber-Straße 12, 14163 Berlin, Germany www.bizol.com



Instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for a specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.