

## Benefits

1. prolonged engine life
2. reduced oil consumption
3. improved fuel economy

## Product Description

**BIZOL Moto 5W-40** four-stroke engine oil for motorcycles and quads is a low viscosity oil based on the HC synthesis technology of the current specification JASO MA2. The special formulation for motorcycle wet clutches ensures optimum performance. High quality base oils and additives reduce deposits and prevent the engine oil sludging. Good corrosion protection properties, savings of fuel and reduced oil consumptions are further advantages of this modern motorcycle oil.



## Base Oil

HC-Synthetic

## Specifications/Approvals & Recommendations

API SN | JASO MA-2

## Available Packages

1 L Art. 18520

4 L Art. 18526

## Technical Data

Name	Value	Method
Viscosity class SAE	5W-40	
Viscosity at 40 °C	87,0 mm <sup>2</sup> /s	ASTM D 7042
Viscosity at 100 °C	14,3 mm <sup>2</sup> /s	ASTM D 7042
Viscosity index	172	ASTM D 2270
Density at 15 °C	860 kg/m <sup>3</sup>	DIN EN ISO 12 185
Pour Point	-39 °C	ISO 3016
ASTM colour number	L4,0	ASTM D1500

## Technical Data

Name	Value	Method
Flash Point (Cleveland)	>200 °C	ISO 2592
Total base number (TBN)	10,8 mg KOH/g	ASTM D 2896