BIZOL Pro Central Hydraulic Fluid+ p90

Martin-Buber-Straße 12, 14163 Berlin, Germany www.bizol.com

Benefits

- 1. a stable power transmission over a wide temperature range
- 2. long-lasting protection from corrosion
- 3. optimum stability against aging

Product Description

BIZOL Pro Central Hydraulic Fluid+ p90 (CHF) is formulated with highly refined HC-Synthetic base oils and high quality additives. It offers a very good thermal stability and aging resistance as well as optimum foaming properties. In addition to its excellent high and low-temperature behavior from -40 °C up to +130 °C **BIZOL Pro Central Hydraulic Fluid+ p90** (CHF) offers a high amount of corrosion protection components as well as maximum wear protection.

Specifications/Approvals & Recommendations

MB 343.0/344.0 | Pentosin CHF202 | VW G 004 000 | GM 1940 766 | Saab 93 1605 48 | Citroen 9979 A1 | Land Rover Cold Climate PAS Fluid 14315 LRN 2261 | Volvo 30741424

Available Packages

1 L Art. 89810* *DE / EN / FR / ES

Technical Data

| Name | Value | Method |
|---------------------|---------------|-------------------|
| Colour | green | |
| Viscosity at 40 °C | 21,0 mm²/s | ASTM D 7042 |
| Viscosity at 100 °C | 6,5 mm²/s | ASTM D 7042 |
| Viscosity index | 300 | ASTM D 2270 |
| Density at 15 °C | 830 kg/m³ | DIN EN ISO 12 185 |
| Pour Point | -69 °C | ISO 3016 |

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for a specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.

