BIZOL Brake Fluid DOT 4

Martin-Buber-Straße 12, 14163 Berlin, Germany www.bizol.com

Benefits

- 1. high safety reserve thanks to increased boiling point
- 2. exceptional braking performance
- 3. long-lasting protection of all brake components

Product Description

BIZOL Brake Fluid DOT 4 is a fully synthetic high-performance brake fluid for the use in all hydraulic brake systems of passenger cars and commercial vehicles. Because of the optimum combination of the synthetic base with a modern additive package, it reliably protects from corrosion as well as oxidation. Extends the life cycle of the components of brake systems. Demonstrates outstanding wet and dry boiling points, which guarantee secure braking. Also suitable for the application in brake systems with antilock (ABS). Does not damage metal, plastic and rubber.

Specifications/Approvals & Recommendations

DOT 4 | SAE J 1703/J 1704 | ISO 4925 | JIS K 2233 Chrysler FMVSS 116 DOT 4 | BMW | VW | GM | Nissan

Available Packages

0,5 L Art. 87420* 0,5 L Art. 77420*

Technical Data

Name	Value	Method
Boiling point (dry)	263 °C	
Boiling point (wet)	163 °C	
Density at 20°C	1,03 g/cm ³	

Instructions

Please follow the operating instructions of the vehicle and engine manufacturer.



The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for a specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.