

QUIETSCH-EX, QUIETSCH-EX Spray

Universal Fluid



Benefits for your application

- Prevents squeaking and sticking
 - Good penetrating properties
 - Protects against corrosion
 - Loosens rust
 - Protects against freezing
 - Cleaning effect
 - Facilitates saw and drill working
-

Description

QUIETSCH EX removes squeaking and sticking of components. It can also be used as universal fluid outperforming ordinary lubricating oils.

Application

For industry, workshops, automobiles, motorcycles.

Used as **lubricating oil**, for bearings, slideways, chains, locks and hinges. A thin film is sufficient to reduce friction and wear.

Used as **penetrating oil**, QUIETSCH EX penetrates well into cracks and even reaches friction points of difficult access.

Used as **rust remover**, QUIETSCH EX loosens rust on screws, hinges and bolts such that they can be undone without damage. The fluid spreads quickly and penetrates into the surfaces. Light rust will be loosened rapidly but heavy rust will require a wait.

Used as **anticorrosion agent**, QUIETSCH EX protects machinery, equipment, tools, vehicles etc. that are not used for a longer period of time (e.g. in winter time) reliably against corrosion.

Used as **freezing protection**, QUIETSCH EX prevents freezing of locks, cables, car doors, gates etc. at temperatures as low as -30°C (if applied on parts beforehand).

Used as **cleaning oil**, for heavily contaminated machine elements, QUIETSCH EX penetrates into machine parts and removes dirt.

Used as **cutting oil**, QUIETSCH EX ensures clean cutting and precision drilling in synthetic materials and metal. A small quantity of this universal fluid on the saw or drill is sufficient to make the tool cut easier through the material. This facilitates work and extends the tool's service life.

Application notes

Spray the spots to be treated shortly with QUIETSCH EX, apply it by brush or let it drip on.

Minimum shelf life

The minimum shelf life is approx. 36 months from the date of manufacture if the product is stored in its unopened original container in a dry, frost-free place.

Material safety data sheets

Material safety data sheets can be downloaded or requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.



QUIETSCH-EX, QUIETSCH-EX Spray

Universal Fluid

Pack sizes	QUIETSCH-EX	QUIETSCH-EX Spray
Aerosol can 50 ml	-	+
Aerosol can 250 ml	-	+
Canister 20 l	+	-
Drum 200 l	+	-

Product data	QUIETSCH-EX	QUIETSCH-EX Spray
Article number	047119	081071
Kinematic viscosity, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 40 °C	approx. 37 mm ² /s	approx. 37 mm ² /s
Colour space	brown	brown
Appearance	clear	clear
Pour point, DIN ISO 3016	<= -35 °C	<= -35 °C

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

**Klüber Lubrication München KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.**

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München KG and if source is indicated and voucher copy is forwarded.



a company of the Freudenberg Group