



Показатели деятельности

- AFNOR: NF E 48-603 HM
- AFNOR: NF E 48-690
- AFNOR: NF E 48-691
- CINCINNATI: MACHINE P-70 (ISO 46)
- DENISON: HF-2 HLP
- DIN: 51524 Part 2
- EATON VICKERS: I-286-S
- EATON VICKERS: M-2950-S
- ISO: 11158, HM
- ISO: 6743-4, HM

HYDRO HLP HM 46

A mineral oil, specifically designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.



Приложения

This oil is specifically designed to satisfy the requirements of the manufacturers of hydraulic systems where the highest demands are made concerning high pressure, temperatures or speeds. It is recommended for the hydraulic systems of the following types : Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydrexco and Worthington. It is also suitable for the lubrication of workshop equipment, reducing gears, bearings, compressed air systems and air screw compressors.

Характеристики

	Unit	Average Value
Плотность при 15 °C	g/ml	0.872
Вязкость при 40 °C	mm ² /s	46.0
Вязкость при 100 °C	mm ² /s	6.97
Коэффициент вязкости		110
Температура вспышки по Кливланду	°C	220
Температура застывания	°C	-30
Кислотность	mgKOH/g	0.40
Содержание сульфатной золы	%	0.06

Упаковка

