



Официально одобрено

- | MB: 229.52
- | GM: DEXOS 2

Показатели деятельности

- | ACEA: C2/C3
- | API: SN/CF
- | BMW: LONGLIFE-04
- | VW: 502 00
- | VW: 505 00
- | VW: 505 01
- | Opel: 0V0401547
- | GM: DEXOS 2
- | MB: 229.51
- | MB: 229.52
- | RENAULT: RN17 Level

SYNTH-DX 5W30

This is a full synthetic lubricant based on carefully selected very high quality base oils, formulated using the latest technology for Mid SAPS catalyst compatible engine oils. Its special formulation combines fuel economy with an extended service life. The reduced ash formulation protects particulate filters and exhaust after-treatment devices (Compatible with DPF).



Приложения

This dexos 2TM approved oil is required for all new GM/Opel/Vauxhall/Chevrolet diesel and gasoline models. GM/Opel has advised that the dexos 2TM specification is backward compatible to older GM/Opel specifications (GM-LL-A-025 and GM-B-LL-025). The majority of GM/Opel/Vauxhall/Chevrolet diesel and gasoline vehicles can use dexos 2TM lubricants. C2* meets all engine protection requirements of ACEA C2.

Характеристики

	Unit	Average Value
Плотность при 15 °C	kg/l	0.851
Вязкость при 40 °C	mm ² /s	72.60
Вязкость при 100 °C	mm ² /s	12.50
Вязкость при минус 30 °C	mPas	6136
Коэффициент вязкости		172
Температура вспышки по Кливленду	°C	230
Температура застывания	°C	-36
Общее щелочное число	mgKOH/g	7.4
Содержание сульфатной золы	%	0.78

Упаковка

