



Full Synthetic GL-5 Gear Oils

Coastal Full Synthetic GL-5 Gear Oils are multi-purpose gear lubricants designed for API Service Classification “GL-5” and “MT-1”.

Coastal Full Synthetic GL-5 Gear Oils are compounded with highly refined synthetic base stocks and additives to ensure extreme pressure characteristics, anti-wear, corrosion inhibition, rust preventions, low pour point, and anti-foaming performance. These products are formulated for use in limited slip differentials.

Coastal Full Synthetic GL-5 Gear Oils may be used in applications calling for API GL-5, API MT-1, SAE J2360, and Mack GO-J (75W-140) and Mack GO-J Plus (75W-90).

Coastal Full Synthetic GL-5 Gear Oils are recommended for use in limited slip and conventional differentials of heavy-duty trucks, cars, light trucks and sport utility vehicles. Always check owner’s manual for proper recommendation. Note: These products are NOT approved for Dana (formerly Eaton Roadranger) and ArvinMeritor Extended Warranties. For those applications use Lubriguard Heavy Duty Synthetic Gear Lubricants.

Benefits

- Reduced wear
- Long service life
- Exceptional low temperature performance
- Reduces drag for optimum fuel economy
- Full Limited Slip performance



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



Full Synthetic GL-5 Gear Oils

Typical Characteristics:

SAE Viscosity Grade	75W-90	75W-140
Pour Point Deg F.	-46	-40
Flash Point, COC, °F	410	420
Viscosity		
@ 40°C, cSt	100	175
@100°C, cSt	15.4	26.2
Viscosity Index	163	186
Specific Gravity @ 60°F	0.865	0.864
Density (lbs/gal)	7.19	7.18
Rust Test, ASTM D665	Pass	Pass
Product Code #		
Bulk	158000	168000
Drum	158019	168019
Keg	158018	168018
Pail	158017	168017
12/1 Quart	158001	168001



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301