



# LubriGold Full Synthetic SAE 0W-20 API SP Motor Oil Approved for dexos1™ Gen 3

---

**Coastal LubriGold Full Synthetic SAE 0W-20 API SP Motor Oil** is approved for **GM dexos1™ Gen 3**. This top tier, high detergent automotive engine oil is specially formulated to meet the stringent lubrication requirements of today's modern engines. It is formulated to provide maximum wear protection and premium performance in all vehicles, especially those with start/stop technology and Hybrids. This full synthetic formulation is engineered to deliver maximum fuel economy in passenger cars, sport utility vehicles, vans and light duty trucks powered by gasoline engines. Synthetic base oils combine with carefully selected additives are used to provide maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge, and varnish. LubriGold's advanced chemistry provides the ultimate emission system, turbocharger, pre-ignition, and timing chain protection.

**Coastal LubriGold Full Synthetic SAE 0W-20 API SP Motor Oil** is a licensed **GM dexos1™ Gen 3** product (GM License # D325BBDE028) GM dexos1™ Gen 3 meets or exceeds GM dexos1™ Gen 2, GM 6094M, Ford WSS-M2C962-A1 and FCA/Chrysler MS-6395. Meets Toyota, and Honda Service Fill Specifications. Meets or exceeds API Service Category SP, SN PLUS, SN, SM, SL and ILSAC GF-6A requirements.

## Benefits

- Maximum Fuel Economy
- Outstanding deposit & oxidation protection
- Exceptional sludge performance
- Robust protection against LSPI events
- Our highest level of protection for thermal and oxidation stability
- ILSAC GF-6A Resource Conserving



**Warren Oil Company, LLC**

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:  
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



**LubriGold Full Synthetic SAE 0W-20 API SP  
Motor Oil  
Approved for dexos1™ Gen 3**

**Typical Characteristics:**

<b>SAE Grade</b>	<b>0W-20</b>
API Gravity @ 60°F	35.0
Sp. Gr. @ 60°F	0.846
Flash, COC, °F	440
Pour Pt., °F	-50
Viscosity,	
cSt @ 40°C	49.2
cSt @ 100°C	8.8
Viscosity Index	159
API Performance	SP
ILSAC	GF-6A
GM dexos1™ Gen 3 License Number	D325BBDE028



**Warren Oil Company, LLC**

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;  
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301