

# LONG-TERM PERFORMANCE MEETS PRODUCTIVITY

**ARALDITE® 9102  
Adhesive can reduce  
costs and boost  
productivity in panel  
bonding applications.**

Manufacturers today are striving to cut costs and improve productivity without compromising performance. When you choose to bond with ARALDITE® 9102 Adhesive, you can maximize coverage with less material because our adhesive spreads more easily than competitive products on the market.

Our adhesive is easy to work with and requires minimal preparation – you simply mix, pour, and start spreading, which saves you valuable time on the assembly floor. It's also meter-mix dispensable, which means you can easily automate your assembly line.

Over time, other bonding materials or mechanical fasteners can cause delamination or distortion when exposed to extreme temperatures and water. ARALDITE® 9102 Adhesive can withstand exposure to temperature, weather extremes, and UV light. It's well-suited for bonding exterior architectural panels, porcelain counters, and panels for mass transportation applications. In addition, ARALDITE® 9102 Adhesive complies with Flame, Smoke, and Toxicity (FST) requirements for passenger rail cars in the US, Europe, and China.



**MADE POSSIBLE**

## WHAT MAKES ARALDITE® 9102 PANEL BONDING ADHESIVE DIFFERENT?

ARALDITE® 9102 Adhesive is a two-component, room-temperature curing structural adhesive specifically designed for panel-bonding applications requiring excellent aging and thermal-cycling resistance.

**PROPERTIES**

**↑2,900** psi

Shear strength on AI at RT up to 2,900 psi

<b>80</b> mins	<b>3.5</b> N/mm
Pot life at RT	T peel strength


**200**°F

Maximum continuous operating temperature

**551,143** psi


Tensile modulus

**LOWER COSTS**



Less adhesive is required, which saves resources and costs


**IMPROVED PRODUCTIVITY**



Quick and easy to use, you simply mix, pour, and start spreading. The adhesive is also meter-mix dispensable, enabling you to automate your assembly line



Scan or click for more information:



### Legal information

All trademarks mentioned are either property of or licensed to Huntsman Corporation or an affiliate thereof in one or more, but not all, countries. Sales of the product described herein ("Product") are subject to the general terms and conditions of sale of either Huntsman Advanced Materials LLC, or its appropriate affiliate including without limitation Huntsman Advanced Materials (Europe) BVBA, Huntsman Advanced Materials Americas LLC, or Huntsman Advanced Materials (Hong Kong) Ltd. or Huntsman Advanced Materials (Guangdong) Ltd. ("Huntsman"). The following supersedes Buyer's documents. While the information and recommendations included in this publication are, to the best of Huntsman's knowledge, accurate as of the date of publication, NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHTS, OR WARRANTIES AS TO QUALITY OR CORRESPONDENCE WITH PRIOR DESCRIPTION OR SAMPLE, AND THE BUYER ASSUMES ALL RISK AND LIABILITY WHATSOEVER RESULTING FROM THE USE OF SUCH PRODUCT, WHETHER USED SINGLY OR IN COMBINATION WITH OTHER SUBSTANCES. No statements or recommendations made herein are to be construed as a representation about the suitability of any Product for the particular application of Buyer or user or as an inducement to infringe any patent or other intellectual property right. Data and results are based on controlled conditions and/or lab work. Buyer is responsible to determine the applicability of such information and recommendations and the suitability of any Product for its own particular purpose, and to ensure that its intended use of the Product does not infringe any intellectual property rights. The Product may be or become hazardous. Buyer should (i) obtain Material Safety Data Sheets and Technical Data Sheets from Huntsman containing detailed information on Product hazards and toxicity, together with proper shipping, handling and storage procedures for the Product, (ii) take all steps necessary to adequately inform, warn and familiarize its employees, agents, direct and indirect customers and contractors who may handle or be exposed to the Product of all hazards pertaining to and proper procedures for safe handling, use, storage, transportation and disposal of and exposure to the Product and (iii) comply with and ensure that its employees, agents, direct and indirect customers and contractors who may handle or be exposed to the Product comply with all safety information contained in the applicable Material Safety Data Sheets, Technical Data Sheets or other instructions provided by Huntsman and all applicable laws, regulations and standards relating to the handling, use, storage, distribution and disposal of and exposure to the Product. Please note that products may differ from country to country. If you have any queries, kindly contact your local Huntsman representative.

ARALDITE® is a trademark of Huntsman Corporation or an affiliate thereof in one or more, but not all, countries.  
© 2023 Huntsman Corporation. All rights reserved.

### Americas

Huntsman Advanced Materials  
Americas LLC  
10003 Woodloch Forest Drive  
The Woodlands, TX 77380, USA  
Tel.: +1 888 564 9318  
Fax: +1 281 719 4047



### Asia Pacific & India

Huntsman Advanced Materials  
(Guangdong) Co., Ltd.  
Shanghai Branch Office  
455 Wenjing Road, Minhang District  
Shanghai 200245, P.R. China  
Tel: +86 21 3357 6588  
Fax: +86 21 3357 6547

### Europe, Middle East & Africa

Huntsman Advanced Materials  
(Switzerland) GmbH  
Klybeckstrasse 200  
P.O. Box  
4002 Basel, Switzerland  
Tel.: +41 61 299 1111  
Fax: +41 61 299 1112